

Principal dimensions				Designation
Outside diameter spacer ring	Nominal housing bore diameter	Operating width	Diameter sealing lip	
d_1 max. mm	D	B_1	d_2 max.	
33.22	47.88	8.38	40.01	33.2x47.3x11.8 TP
36.47	51.99	8.31	44.45	36.5x51.4x11.7 TP
38.05	55.04	9.6	46.99	38.1x54.4x12.8 TP
41.86	59.77	9.25	50.04	42.0x59.1x12.8 TP
42.52	59.79	10.69	51.05	43.1x59.4x14.3 TPM
44.6	63.04	10.69	53.7	44.7x62.7x14.2 TP
45.69	62.99	10.69	54.71	46.3x62.3x14.3 TPM
46.2	64.64	10.8	56.41	46.1x64.1x14.1 TP
50.29	67.59	10.8	58.42	50.3x67.0x14.7 TP
52.43	70.1	10.8	61.11	53.0x69.3x14.2 TPM
52.6	70.79	10.8	61.34	52.7x70.5x14.2 TP
54.99	72.75	10.8	64.19	54.9x72.4x14.8 TP
58.19	75.54	10.67	67.03	58.1x75.0x14.7 TP
58.9	77.65	11.1	67.59	58.8x77.1x15.2 TP
61.09	82.55	11.1	70	61.1x82.0x16.0 TP
63.14	83.74	15.49	73.66	63.2x83.1x19.3 TP
63.6	83.49	11.13	74.22	63.6x82.5x15.0 TP
67.21	87.25	11.13	77.14	67.1x86.7x15.4 TP
76.71	99.8	11.1	89.08	76.7x99.3x15.1 TP
80.72	106.2	11.1	92.53	80.8x105.8x15.9 TP